

Työpöytänäyttö

SHARP / NEC MULTISYNC EA272F



Tehoa työpisteen yhteyksiin.

- Haluttu näytön koko – suosittu 27,0 tuuman näyttö Full HD -resoluutiolla on täydellinen koko kiireisiin toimistoihin.
- Sotkuton työpiste – tehokas 65 W:n USB-C-liitäntä, ja se hoitaa videon, äänen, virran ja USB-liitännän yhdellä kaapelilla.
- Tulevaisuutta varten valmis joustavuus – laaja yhdistettävyyys tarjoaa suuren joustavuuden DP-, HDMI-, USB-C-, USB-A- ja audiolähdöllä.
- Helppo usean näytön käyttö – ketjuta useita näyttöjä DisplayPort-lähdön kautta tarvitsematta lisäkaapeleita.
- Terveysten ja hyvinvoinnin huomioiminen – loistava ergonominen korkeussäätö välillä 0 - 150 mm; sisäänrakennettu Low Blue Light- ja Flicker-Free-teknologia; lisäksi integroitu ympäristön valoanturi.

Määrittelyt

Paneelin tekniikka	AH-IPS LCD with LED backlight
Kuvasuhde	16:9
Kirkkaus (cd/m ²)	250
Kontrastisuhde	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
Näytön värit	16.78
Vasteaika (harmaa harmaaseen ka) ms	6
Pikseliväli (mm H/V)	0,311
Energy Efficiency	Ambient light sensor, Auto brightness, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 15 kWh/1000 h, Energy efficiency class: D, Human sensor, LED backlight technology
Ecological Standards	Efficient mechanical design for minimised packaging, Minimal use of harmful material
Ecological Materials	ErP compliant, WEEE
Height adjustable stand [mm]	150
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	360
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	610
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	628
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	377
[AVSpecificationLandscapeDimensionsHeightMaxMm]	527
Optimum Resolution	1920 x 1080 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 720 x 400 (70 Hz), 800 x 600
Lisävarusteet	
Shipping Content	Control Sync Cable, DisplayPort Cable, Monitor, Power Cable, Setup Manual, Setup Guide, USB cable, USB-C Cable
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.1 (3 down / 1 up), USB Type C
Analog	VGA
Bezel-koko (L/R) mm	1
Bezel-koko (U) mm	1
Bezel-koko (L) mm	16
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	55 - 75

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	DDC2B/2Bi, EDID Standard, VESA DDC/CI
Audio	Headphone Jack, Integrated Speakers (1 W + 1 W)
Adjust Functions	Audio Volume / Lock-Out, Auto Adjust, Brightness, Colour Temperature Control, Contrast, Control Sync, DV Mode, EcoMode, Factory Preset, Fine Adjust (analog), Human Sensing, Intelligent Power Management, Language Select, Monitor Information, NTA (Non-Touch-Auto-Adjustment), On-Screen-Display (OSD) lock-out, One Touch Recovery, Power-Off Timer, sRGB CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class 2), ISO 9241-307 (pixel failure class 1), Low Blue Light, PSB, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA, TCO Edge 2
Safety & Ergonomics	3 years warranty incl. backlight, Optional 4th to 5th year warranty extension
Rajoitettu valmistajan takuu (v)	3 years warranty incl. backlight, Optional 4th to 5th year warranty extension
Special Characteristics	DDC/CI compatible, RGB Support, Frame Comp, PJLink Support, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Touch Sensor Keys, USB ver. 3.0 (3 down / 1 up)
Käyttölämpötila (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Lävistäjän koko (tuumaa/cm)	27
Lävistäjän koko (tuumaa/cm)	69
Colour Gamuts	102 % sRGB, 75.5% AdobeRGB, 72% NTSC
Virrankulutus päällä -tila (IEC62087:2012)	15 (Eco Mode 2), 21 (typ.)
Power Supply	0.85 A/0.45 A, 100-240 V, Integrated Power Supply
Kiinnitys (VESA/kohtien lukumäärä/väli mm)	100 x 100
Kensington-lukko	True
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp / NEC MultiSync EA272F, 28/5/2026