

Entry level A3 colour MFP

BP-20C20

A3 colour MFP that supports the small office environment



- Entry level 20ppm full colour A3 MFPs with 600 x 600 dpi print resolution
- Full-colour network scanning with multiple scan destinations
- Red and green LEDs to notify users of machine/job status from a distance
- 100-sheet Reversing Single Pass Feeder scans documents at up to 37ipm^{*2}
- Sharpdesk Mobile print application^{*3} enables files on a mobile device to be printed
- Direct printing of PDF/TIFF/JPEG files
- Compact, cubic design with the smallest A3 device footprint^{*1} in the market
- Tiltable control panel with 4-inch, 5-line mono LCD
- Standard paper tray, as well as multi bypass tray, accommodates a wide variety of paper sizes, including A6 and A3W
- USB port conveniently located at the front of the MFP allowing easy printing from or scanning to the USB drive
- Optional wireless connectivity enables easy access from mobile devices and flexible MFP placement
- ID Card Copy function with dedicated key enables easy copying of both sides of a card onto a single page

*1 'Footprint' refers to the floor or desk space occupied by the device for A3 colour laser MFPs at the time of publishing. *2 Images per minute; when feeding A4 one-sided sheets. *3 Availability varies by country/region.

www.sharp.fi

SHARP
Be Original.

Määrittelyt

YLEISTÄ

Nopeus värikopioita/-tulosteita minuutissa (A4)	20
Nopeus mustavalkokopioita/-tulosteita minuutissa (A4)	20
Nopeus värikopioita/-tulosteita minuutissa (A3)	12
Nopeus mustavalkokopioita/-tulosteita minuutissa (A3)	12
Paperikoko: Min-Max	A6 - A3W
Paperin paino (g/m ²)	60 - 256
Paperikapasiteetti: vakio (arkkia)	350
Paperikapasiteetti: max. (arkkia)	1850
Lämpenemisaika (sek)	29
Kopiokoneen muisti min/max (GB)	2
Kaksipuolisuus	STD
Käyttöjännite - paikallinen nimellijännite (Hz)	220 - 240V, 50 / 60Hz
Virrankulutus (kW)	1.84
Mitat (L x S x K) (mm)	560 x 560 x 653
Paino (kg)	52

VERKKOSKANNERI

Resoluutio (dpi)	600 x 600
------------------	-----------

FAKSI

Pakkausmenetelmä	MH / MR / MMR / JBIG
Yhteysprotokolla	Super G3 / G3
Modeemin nopeus (bps)	33600 - 2400
Skannausleveys (max.)	A3

VÄRIN KESTO

Musta (sivua 5% peiton perusteella)	18000
Syaani (sivua 5% peiton perusteella)	10000
Magenta (sivua 5% peiton perusteella)	10000
Keltainen (sivua 5% peiton perusteella)	10000

KOPIOKONE

Alkuperäisten paperikoko (max.)	A3
Ensimmäinen mustavalkokopio (sek)	8.0
Elektroninen lajittelu	STD
Sarjakopiointi (max. arkkimäärä)	999
Skannausresoluutio (dpi)	600 x 600, 600 x 400
Tulostusresoluutio (dpi)	600 x 600
Sävyt (vastaavat tasot) - mustavalko	256
Zoom (%)	25 - 400
Valmiit kopiosuhteet	10

TULOSTIN

Resoluutio (dpi)	600 x 600
Liitäntä	USB 2.0, 10Base-T / 100Base-TX / 1000Base-T
Tuetut käyttöjärjestelmät	STD: Windows Server 2008, 2008R2, 2012, 2012R2, 2016, Windows 7, 8.1, 10 OPT: Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 10.14

PDL-tulostinemulointi vakio/lisävaruste	STD: PCL6 OPT: PostScript 3 emulation
---	---------------------------------------

LANGATON LAN

Langaton LAN (vakio/lisävaruste)	OPT
----------------------------------	-----

Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Mac is a trademark of Apple Inc. registered in the US and other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. PCL is a registered trademark of Hewlett-Packard Company. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation May 2019. Ref:BP-20C25 Datasheet. All trademarks acknowledged. E&OE.