

Desktop display

# Sharp / NEC MultiSync EA271U



- Uusin USB-C-liitettävyys – optimoi yhdistettävyys ja korvaa video-, ääni-, virta- ja USB-kaapelit yhdellä kaapelilla kannettavan tietokoneen/tabletti-PC:n liittämiseksi näyttöön.
- Paras muoto ja toiminta – tulevaisuutta varten valmis design 3-puoleisella ultrakapealla kehyksellä tekee toimiston sisustuksesta raikkaan ja ammattimaisen.
- Helppo usean näytön hallinta – hallitse jopa 8 näytön asetuksia usean näytön kokoonpanossa päänäytöllä ControlSync®-teknologian avulla.
- Terveysten ja hyvinvoinnin huomioiminen – loistava ergonominen korkeussäätö välillä 0 - 150 mm; sisäänrakennettu Low Blue Light- ja Flicker-Free-teknologia; lisäksi integroitu ympäristön valoanturi.
- Automaattisesti säätyvä virrankulutus – tarpeettoman virrankulutuksen minimoimiseksi ihmisen ja ympäristön valon tunnistuksen anturit säätelevät näytön kirkkautta käyttäjän mieltymysten ja tilan valaist

# Specifications

## DISPLAY

Panel Technology	IPS TFT with W-LED backlight
Screen Size [inch/cm]	27 / 68
Pixel Pitch [mm]	0.155
Brightness (typ.) [cd/m <sup>2</sup> ]	350
Contrast Ratio (typ.)	1300:1 (9000:1 dynamic contrast ratio)
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	5
Colours [Mio.]	1064.64332261
Screen Aspect Ratio	16:9
Colour Gamuts	110 % sRGB; 81.6% AdobeRGB, 78% NTSC

## RESOLUTION

Optimum Resolution Supported	3840 x 2160 at 60 Hz 1024 x 768; 1152 x 864; 1280 x 1024; 1600 x 1200; 1920 x 1080; 1920 x 1440; 2560 x 1440; 3840 x 2160; 640 x 480; 800 x 600; 832 x 624
------------------------------	--

## ELECTRICAL

Power Consumption on Mode [W]	150 (max.); 30 (Eco Mode 1); 38 (Eco Mode 2); 38 (shipping)
Power Savings Mode [W]	0.33
Power Supply	1.6 A / 0.75 A; 100-240 V; integrated power supply

## ERGONOMICS

Screen Tilt [°]	-5 to 35
Height adjustable stand [mm]	150 (Landscape mode)
Screen Swivel [°]	-170 to +170
Screen Rotate [°]	-90 to 90 (landscape to portrait mode)

## MECHANICAL

Bezel Width [mm]	1 (left and right); 1 (top)
Dimensions (W x H x D) [mm]	361.9 x 628.6 - 652.1 x 250 (Portrait mode); 611.8 x 378 - 528 x 250 (Landscape mode)
Weight [kg]	9.5
VESA Mounting [mm]	100 x 100

## SYNCHRONISATION RATE

Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	30 - 75

## CONNECTIVITY

Digital	1 x DisplayPort; 1 x USB Type C (60 W); 2 x HDMI; USB ver. 3.1 (3 down / 1 up)
---------	--

## ENVIRONMENTAL CONDITIONS

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 85
Storage Temperature [°C]	-10 to 60

## ADDITIONAL FEATURES

Special Characteristics	Advanced NTAA; Ambient light sensor for optimized brightness levels; ControlSync®; Customize Setting; DDC / CI compatible; DICOM simulation; EcoModes; ErgoDesign®; Height adjustable stand (150 mm) with 90° Pivot features; Human Sensor; LED Backlight Technology; Picture-by-Picture; Quick release Stand and Handle; Versatile and easy installation (VESA standard) with NaViSet and NaViKey Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
Colour Versions	•
Cable Management	•
Kensington security slot	•
Plug and Play	EDID Standard; VESA DDC2Bi; VESA DDCi
Audio	1W + 1W (De-activateable); Headphone Jack
Adjust Functions	DV Mode; EcoMode; Human Sensing; Intelligent Power Management; sRGB
Shipping Content	Control Sync Cable; Display; DisplayPort cable; Power Cable; Set-up Manual; USB Cable
Safety and Ergonomics	CE; EAC; ErP; Flicker-free; ISO 9241-307 (pixel failure class I); Low Blue Light; PSB; RoHS; TÜV Ergonomics; TÜV GS; UL / C-UL or CSA
Warranty	3 years warranty incl. backlight; optional 1st to 3rd year 24 / 7 usage warranty; optional 4th to 5th year warranty extension
GREEN FEATURES	
Energy Efficiency	Ambient light sensor; Carbon Footprint Meter / Carbon Savings Meter; EcoMode; Energy consumption: 22 kWh / 1000 h; Energy efficiency class: F; Human sensor; LED backlight technology
Ecological Standards	Minimal use of harmful material
Ecological Materials	Energy Star 8.0; ErP compliant; RoHS compliant; TCO 8.0

