

Desktop Display

Sharp/ NEC MultiSync E274FL



- Paranna tuottavuuttasi – sulautetun LAN:n ja USB-C:n ansiosta tämä näyttö toimii telakointikeskittimenä henkilökohtaisessa työtilassasi.
- Suojaa käyttäjien hyvinvointia – sisäänrakennettu Low Blue Light -tekniikka suodattaa pois vaaralliset sinisen valon päästöt, kun taas Flicker-Free-tekniikka eliminoi taustavalon välkkymisen.
- Paras muodoiltaan ja toiminnaltaan – tulevaisuuteen valmis muotoilu, jossa on 3-puolinen erittäin kapea kehys, saatavana mustana tai valkoisena, sekä valinnainen VESA-kiinnityslevy ohuille asiakaslaitteille.
- Tulevaisuuden varma joustavuus – laaja liitettävyyden tarjoaa korkeatasoista joustavuutta LAN-, DP-, HDMI-, USB Type C-, USB A- ja äänilähdön kanssa.
- Ergonominen toimisto – täyden korkeuden säätö (130 mm), kääntö-, kallistus- ja kääntötoiminnot takaavat täydellisen yksilöllisen työtilan asennuksen.

Specifications

DISPLAY

Panel Technology	VA TFT with W-LED backlight
Screen Size [inch/cm]	27 / 69
Pixel Pitch [mm]	0.275
Brightness (typ.) [cd/m²]	250
Contrast Ratio (typ.)	1000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	6
Colours [Mio.]	16.77
Screen Aspect Ratio	16:9

RESOLUTION

Optimum Resolution	1920 x 1080 at 60 Hz
--------------------	----------------------

ELECTRICAL

Power Consumption on Mode [W]	13 (Eco Mode 2); 19 (typ.)
Power Savings Mode [W]	0.3
Power Supply	Integrated power supply

ERGONOMICS

Screen Tilt [°]	-5 to 25
Height adjustable stand [mm]	120
Screen Swivel [°]	170 to -170
Screen Rotate [°]	-90 to 90 (landscape to portrait mode)

MECHANICAL

Bezel Width [mm]	1 (left / right / top); 16 (top and bottom)
Dimensions (W x H x D) [mm]	610.4 x 376.9 - 506.9 x 282.6 (Landscape mode); Without stand: 610.4 x 359.9 x 46.6
Weight [kg]	With stand: 8.2; Without stand: 5.1
VESA Mounting [mm]	100 x 100

SYNCHRONISATION RATE

Horizontal Frequency [kHz]	31.5 - 81
Vertical Frequency [Hz]	50 - 75

CONNECTIVITY

Digital	1 x DisplayPort; 1 x HDMI; 1 x USB Type C (60 W); USB ver. 3.1 (3 down / 1 up)
Output Control	1x LAN / RJ45

ENVIRONMENTAL CONDITIONS

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 85
Storage Temperature [°C]	-10 to 60

ADDITIONAL FEATURES

Special Characteristics	Flicker Free; Low Blue Light
Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
Cable Management	•
Kensington security slot	•
Plug and Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable); Headphone Jack
Shipping Content	DisplayPort Cable; Power Cable; Setup Guide; USB-C Cable
Safety and Ergonomics	EnergyStar 8.0; Flicker-free; Low Blue Light; RoHS; TCO 9.0; TÜV Ergonomics; TÜV GS; WEEE
Warranty	3 years warranty incl. backlight
GREEN FEATURES	
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter; ECOMode
Ecological Standards	RoHS compliant; TCO 9.0

