

Digital Signage

Sharp MultiSync M552



Vaativiin opaste- ja kokousympäristöihin M2-sarja tarjoaa monipuolisen ratkaisun, joka yhdistää vaikuttavan suorituskyvyn ja tehokkuuden.

- Seamless meeting workflows – a single USB-C cable transmits video, data, and power for instant, clutter-free meeting setups and USB-C supports frictionless BYOD experiences.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.1x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Broad AV compatibility – fully interoperable with leading meeting room platforms including Crestron (XiO Cloud), Cisco Webex, Q-Sys, and Microsoft Teams, ensuring effortless integration.

Määrittelyt

Paneelin tekniikka	IPS with Direct LED backlights
Alkuperäinen tarkkuus (Pikseliä)	3840 x 2160
Kuvasuhde	16:9
Taustavalon tekniikka	Direct LED
Kirkkaus (cd/m2)	500
Kontrastisuhde	8000:1
Vasteaika (harmaa harmaaseen ka) ms	8
Pikseliväli (mm H/V)	0,315
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Käyttöjännite (ACV) / taajuus (Hz)	100-240
Käyttöjännite (ACV) / taajuus (Hz)	50-60
Virrankulutus (W) (Käyttö MAKS.)	105
Käyttölämpötila (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	80
Tuotteen paino ilman jalustaa (Kg)	21
Lähetyspaino (Kg)	27
Näytön portti	1
HDMI	2
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Energiatähti	True
Audio 3,5 mm liitin	1

Special Characteristics	DICOM Simulation, CEC Support, HDMI ARC, Scheduler
24/7 toiminta sertifioitu	True
Paikallinen himmennys	True
Virranhallinta	True
Laitetila (Kiinnitys)	True
Kaapin väri	Black
Lämpötila-anturi	True
Kirkkauden anturi	True
Aikatauluttaja / Ajastin	True
Etähallinta	True
Maisema	True
Omakuva	True
Vaakasuunta	Horizontal
Kiinnitys (VESA/kohtien lukumäärä/väli mm)	300 x 300 (FDMI)
Kiinnitysruuvin tekniset tiedot (Koko/Maksimipituus)	M6
Bezel-koko (L/R) mm	11
Bezel-koko (U) mm	11
Bezel-koko (L) mm	14
Lävistäjän koko (tuumaa/cm)	54
Lävistäjän koko (tuumaa/cm)	138
Rajoitettu valmistajan takuu (v)	3 years warranty incl. backlight
Haze Level [%]	Pro 25



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync M552, 14/7/2026